

# VM Reference Card 1.5.1

(for VM 6.63 and beyond)  
<http://www.wonderworks.com/vm/>

## Starting VM

start VM M-x vm

VM will copy your mail from the spool-directory (`/var/mail`) to your home-directory into a file called `IMBOX`.

## Exiting VM

**quit** VM: folder is saved to disk if it is modified; new messages are marked as unread; folder not expunged q  
**exit** VM with no change to the folder x

## Movement

**next** message n  
**previous** message p  
**Next** message, ignore **skip-variable** N  
**Previous** message, ignore **skip-variable** P  
**next** unread message M-n  
**previous** unread message M-p  
**goto** numbered message (or prefix arg) RET  
**goto** numbered message (or prefix arg) M-g  
**goto** last message seen TAB  
**goto** parent of current message ~  
incremental **search** through folder M-s

## Display

page **forward** or expose message body SPC  
page **backward** b  
**beginning** of current message <  
**end** of current message >  
display hidden **headers** t  
summarize folder contents =

## Deletion

Delete operations flag messages for deletion. To physically delete flagged messages, the folder must be expunged.

**delete** message; prefix arg deletes forward d  
**delete** message; prefix arg deletes backward C-d  
**kill** all messages with same subject as the current k  
**undelete** message flagged for deletion u  
**expunge** deleted messages (without saving folder) #

## Reply, Resend or Mail

**reply** only to the sender r  
**Reply** with original message included R  
**followup** (reply) to all recipients f  
**Followup** with original message included F  
**Bounce** current message (accidentally sent to you) B  
**zoink?** (forward) current message z  
**resend** undelivered message M-r

compose a new **mail** message m  
**continue** composing the most recent message being composed c

## New Mail/Folder

**get** new mail that has arrived in the spool g  
**visit** another mail folder v

## Edit, Save

**edit** current message (C-c C-c to exit) e  
**save** current message to a folder s  
**write** current message body to a file w  
**Save entire** folder (does not expunge) S  
**archive** messages to `vm-auto-folder-alist` folders A  
**junk** (discard) cached information about the current message j

## Digest

**digestify** entire folder @  
**burst** a digest into individual messages, and append and assimilate these messages into the current folder \*

## Sorting

**group** (sort) messages by various keys (? g lists keys) G

## Help

**help** (describe mode) ?  
The VM FAQ is at:  
<http://www.wonderworks.com/vm/FAQ.html>  
Questions may be posted to `gnu.emacs.vm.info`

## Undo

**undo** recent changes in message attributes and labels; C-x u is equivalent (expunges, message edits, and saves cannot be undone) C--

## Virtual folders

A virtual folder contains messages, selected from one or more real folders, fitting certain criteria.

### Create a virtual folder with

some of the **current** folder's messages V C  
all messages matching current **author** V A  
all messages matching current **subject** V S  
some messages by applying selectors of another virtual folder V X

### Miscellaneous

**visit** folder (defined in `vm-virtual-folder-alist`) V V  
**toggle** attribute **mirroring** V M  
**help** for virtual folder commands V ?

## Marks

Some common operations may be performed on several messages at one time. First, mark them (M M) and then perform the operation (d, s, u etc.) on the marked messages, by preceding the operation with M N).

use marks: the next VM command will affect only marked messages if it makes sense for the command to do so M N

**mark** current message M M  
**unmark** current message M U  
**mark all** messages M m  
**unmark all** messages M u

### Messages matching

current **subject** M S **Unmark** M s  
current **author** M A **Unmark** M a  
**region** (point/mark) in the summary M R **Unmark** M r  
virtual folder selector M C **Unmark** M c  
**thread** rooted at the current message M T **Unmark** M t

**toggle** the marked-ness of all messages M V  
**partial** help for mark commands M ?

## Shell

run a shell command !  
pipe current message into shell command |

## Mail aliases

Aliases are memorics that represent long email addresses. They are stored in `~/mailrc`, using either of the following formats:

```
alias luis "elf@ee.ryerson.ca (Luis Fernandes)"
alias luis "Luis Fernandes <elf@ee.ryerson.ca>"
```

Once an alias is created, you can type `luis` instead of the full email address. If new aliases are added to `~/mailrc` while VM is running, you must re-load VM for the aliases to take effect.

### Mailabbrev

Note: for XEmacs 21.1.7 onwards, mailabbrev support is automatic.

Alias expansion (typing the alias followed by `SPC` or `a`, will expand the alias) is available by adding the following to your `~/emacs`:

```
(load-library "mailabbrev")
(add-hook 'mail-setup-hook 'mail-abbrevs-setup)
```

### Big Brother Database

BBDB is a rolodex-like database program, with features like name completion, that is a more sophisticated alternative to mailabbrev. It can be used by both mail readers and news readers.

After installing BBDB, add the following to your `~/vm`:

```
(require 'bbdb)
(add-hook 'vm-mail-mode-hook 'bbdb-define-all-aliases)
(bbdb-initialize 'vm)
(bbdb-insinuate-vm)
```

## Miscellaneous

```
set message attributes      a
add labels to message      1 a
delete labels from message  1 d
reload VM init file, ~/vm   L
change a folder to another type %

Submit a bug report         M-x vm-submit-bug-report
```

## Window configuration

```
save configuration (to a name)  W S
delete configuration           W D
apply configuration            W W
help for window commands       W ?
```

## MIME

You may have to upgrade to the latest version of VM to use these features.

```
save the attachment          $ s
delete the attachment        $ d
view attachment with an external viewer $ e
print the attachment         $ p
pipe the attachment to a command $ |
display using the default display method $ RET
```

## Useful customizations

Some useful customizations (`~/vm`) of VM variables are described here.

```
(setq
  ;;where to save folders
  vm-folder-directory "~/Mail/"
  ;;where to keep IMBOX
  vm-primary-inbox "~/Mail/IMBOX"
  ;;where to save a copy of outgoing email (FCC)
  mail-archive-file-name
    (expand-file-name "~/Mail/outbox")
)
;;: spool dirs (replace LOGIN with your login)
(setq vm-spool-files `("/var/mail/LOGIN"
  "/var/spool/mail/LOGIN"))
(setq
  ;;do not add my email when replying to a cc
  vm-reply-ignored-addresses
    (list (concat "--user-login-name " @"))
  ;; add 'Re' in front of replies
  vm-reply-subject-prefix "Re: "
  ;;outgoing mail from header looks like this
  vm-mail-header-from
    "Luis fernandes <elf@ee.ryerson.ca>"
  ;;location of crash files
  vm-keep-crash-boxes "~/CRASH"
  ;; don't create new frame when...
  vm-frame-per-folder nil
  vm-frame-per-composition nil
  vm-frame-per-edit nil
)
;;:MIME external viewers (Kevin.Cutts@motorola.com)
(setq vm-mime-external-content-types-alist
  '(("image" "xv")
    ("video" "xanim")
    ("application/postscript" "ghostviewer")
    ("application/pdf" "acroread")))
)
```

Copyright © 2000 Free Software Foundation, Inc.  
VM by Kyle Jones  
Reference Card v1.5.1 by Luis Fernandes  
based on a design by Stephen Gildea  
<http://www.ee.ryerson.ca/~elf/vm/>

Permission is granted to make and distribute copies of this card provided the copyright notice and this permission notice are preserved on all copies.